

SUCCESS STORY:

AERZEN USA
Albertville WWTP

ALBERTVILLE WWTP USES BIOGAS BLOWER TO REPLACE NATURAL GAS TO FUEL BOILERS

Background

Albertville, Ala., is a small city on Sand Mountain, a 26-square-mile plateau in the northeast corner of the state. The Municipal Utilities Board (MUB) of Albertville operates the MUB Waste Water Treatment Plant (WWTP), an 11.5 million gallon per day (mgd) facility that serves approximately 20,000 residential and industrial customers in Albertville and the surrounding areas.

As part of an ongoing effort to improve efficiency and lifecycle costs across all of its projects, the MUB set out to upgrade solids handling at the WWTP and pursue Class A biosolids certification, a U.S. Environmental Protection Agency (EPA) designation for dewatered and heated sludge that contains low levels of pathogens. Since Class A biosolids meet EPA guidelines for land application with no restrictions, they can be sold for use as fertilizer or compost for farms and vegetable gardens.

Requirement

The plant has Anaerobic Digesters with a Biogas recovery system which allows the facility to use the Biogas that is rich in methane as a fuel source for the sludge dryer. Plant operators selected new dryer technology for sludge treatment and used multiple sludge-to-water heat exchangers to recover heat and squeeze as much energy as possible out of the system. The facility, which sees an average demand of about 7.5 mgd, already powered its boilers some of the time with methane gas captured from its anaerobic digesters, but during off-peak times, operators relied on natural gas as a secondary fuel to supplement the recovered methane gas.



Segment	Environmental engineering
Problem	WWTP uses fuel boilers
Solution	AERZEN Biogas packages
Results	Reduces operating cost by using biogas solution

AERZEN USA CORPORATION
108 Independence Way
Coatesville, PA 19320
United States
T +1 800-444 1692
T +1 610 380 0244
F +1 610 380 0278
order-usa@aerzencom
www.aerzenusa.com

Contact	Catesha Early T: +1 484-784-9029 catesha.early@aerzen.com
----------------	---

Solution

"We had purchased a dryer, and we were looking to reduce our operating costs by increasing our use of biogas to run our boilers," said Dale Williams, plant manager at the Albertville MUB WWTP. "In the past, we had enough pressure on the gas system during the summer months to power the boilers, but we would need to swap over to natural gas during our low-demand times in the colder months.

Following a standard RFP process, Albertville selected a 30-horsepower Aerzen Biogas Delta Blower package GM 10 S to compress the methane-rich biogas into the holding tank. Designed for landfill, biogas, and natural gas applications, the Biogas Delta GM 10 S is a positive displacement blower is built for safety. At the Albertville facility, the blower takes any Biogas including methane gas not being directed to the dryers, compresses it to 14 PSI, and sends it to the storage vessel. The Biogas is not currently treated and is stored in Gas Holder Covers on the Anaerobic Digesters. Excess Biogas is routed to the Blower and compressed to 14 PSI for storage. The outlet pressure (14 PSI) is the basis of controlling the Blower. The inlet pressure is very low, usually 8-12" WC. Based on the same sound engineering and precision machining as Aerzen's three-lobe positive displacement blowers for conventional applications, Delta biogas blowers are available in 10 package sizes covering intake volume flows of 35 inlet cubic feet per minute (icfm) up to 1,500 icfm, and positive pressure up to 15 psig. For the biogas application, the blower stage features a

gastight driveshaft seal and no absorption materials in the discharge silencer. The ductile iron casing stage, inlet and discharge silencers are TÜV certified and explosion proof up to 174 psig. The blower was shipped completely assembled, so it required no extensive installation work, grouting, or special anchoring. A swing plate attached to the base provides automatic tensioning of the blower belts, using the mass of the motor to maintain tension with no need for adjustments or springs. This feature of the Delta blower not only reduces maintenance requirements, but also reduces the potential for damaging belts or bearings by operating with too little or too much belt tension.

The Conclusion

"Since we've had the biogas blower installed, we're able to maintain a constant pressure on the gas system to ensure that we never switch over to natural gas," Williams said. "On the digester side, we're now able to feed 100 percent biogas all year-round."

The biogas blower's reliable operation allows the Albertville MUB to meet its goal of reducing operational costs by producing its own power at a cost lower than retail energy sources. The utility has also improved its environmental footprint, reducing greenhouse gas emissions and cutting back on overall energy consumption by powering its equipment with a renewable fuel that would otherwise have been flared off as a waste product.



The company

Aerzener Maschinenfabrik GmbH, founded in 1864, is a worldwide leading manufacturer of twin-shaft positive displacement machines and turbo machines. The range of products includes rotary lobe compressors, positive displacement blowers, turbo blowers, screw compressors and gas meters. Aerzener Maschinenfabrik has about 1,800 employees and more than 40 international subsidiaries. The

innovative technological solutions from AERZEN include empirical values of a company history of more than 145 years. Industrial plants all over the world are provided with gaseous media using AERZEN blowers, compressors, turbos and gas meters. Besides standard products the company also develops customer specific special solutions. Moreover, AERZEN offers a wide range of After Sales services - from repair and modernization of existing plants up to Condition Monitoring.



AERZEN
EXPECT PERFORMANCE